



MICRO SIMULATION MODEL TO ANALYZE TURNING MOVEMENT DELAYS AT ROAD INTERSECTIONS



L.W. GAYAN LIYANAGE

This thesis was submitted to the Department of Civil Engineering of the University of Moratuwa in partial fulfilment of the requirement for the Degree of Master of Science.

Supervised By
Professor J.M.S.J. Bandara

624"04"
624 (043)

UM Thesis coll.

University of Moratuwa



82467

Department of Civil Engineering

University of Moratuwa

Sri Lanka

August 2004

82467

82467



DECLARATION


The work included in this thesis in part or whole has not been submitted for any other academic qualification at any institution.



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk



L.W. Gayan Liyanage



Prof. J.M.S.J. Bandara

To My Father and Mother



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

Abstract

In many countries the transportation planning process is currently turning from the unlimited expansion of the infrastructure to the improvement of the efficiency of the existing systems. This demands the development of efficient management tools. Due to the complexity of the problem, many of these tools are computer based models, a development which is reinforced by the explosion of computational power over the recent past.

This research is a development of a micro simulation model to understand delays at intersections. This would give an opportunity to traffic engineers to understand delays at intersections and to evaluate the effectiveness of traffic control measures before implementation. This information is very useful for situations where traffic signals are to be installed and the field trials would be expensive.

Even though there are a large number of variables that contribute to the intersection, three variables that would have considerable impact on intersection performance were selected for modelling. They are Geometric Properties, Vehicle Properties, and Driver Behaviour. Three different lane arrangements, five vehicle types and three driver behaviour situations can be handled by the model.

This model can be used to simulate both controlled and uncontrolled situations of four-way or three-way intersections. Validation of the model with field data was done using field surveys. Model outputs include queue length, vehicle flow, vehicle delay of each approach and graphical representation of vehicle movements.

Acknowledgment

It is my desire to acknowledge my supervisor Professor J.M.S.J.Bandara for his constant encouragement and guidance at all stages of this research without whose invaluable commitment and dedication this research may not have been a reality. The valuable suggestions made by Prof. Amal S. Kumarage, Chairman, National Transport Commission, Dr. Ashok Peiris, Head, Department of Computer Science and Engineering, University of Moratuwa and Dr. Saman Thilakasiri, Senior Lecturer, Department of Civil Engineering, University of Moratuwa are also thankfully acknowledged.

A special thanks goes to the Asian Development Bank for providing financial support for this research through the Science and Technology personnel Development Project and the Director Postgraduate Studies, Dean Faculty of Engineering, Head of Civil Engineering Department, Research Coordinator, Department of Civil Engineering and all the academic staff members of the Department of Civil Engineering for providing the opportunity to complete this research.



I extend my heartfelt gratitude to the Deputy Director (Planning) Mr. Gunathilaka Bandara and his staff of Road Development Authority for providing survey data for the research. The completion of the field survey was made possible due to the enthusiasm and support given by fellow researchers and staff members of the Transportation Engineering Division in the Department of Civil Engineering, especially Damith, Ravihansa, and Siva to whom a special thanks are due. I would like to thank all the staff members of the Transportation Engineering Division and the Computer Service Division in the Department of Civil Engineering for the assistance extended for this research.

Finally, a special thank you goes to Mr.& Mrs. Shanthi Jayakoddy, my dear friends Prabath & Pradeep, my family members for their constant encouragement and support, extended throughout the study, to make this research a reality.

L.W.Gayan Liyanage

Contents

	Page
Abstract	i
Acknowledgement	ii
List of Figures	iii
List of Tables	iv
List of Annexes	vi

Chapter One	- Introduction	1-6
-------------	-----------------------	------------

1.1 Objective of the Research	2
1.2 Traffic as a Simulation Object	2
1.3 Areas and Approaches in Traffic Simulation	5
1.4 Limitation of the Model Developed	5
1.5 Organization of the Thesis	6



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

Chapter Two	- Literature Review	7-19
-------------	----------------------------	-------------

2.1 Micro-simulation	7
2.2 Simulation Development in the Recent Past	8
2.3 Why undertake Micro-Simulation Models	9
2.4 Level of Details in Simulations	9
2.5 Scale of the Independent Variables	11
2.6 Representation of the Processes	11
2.7 Operationalization	11
2.8 Scale of the Applications	11
2.8.1 Microscopic Simulation Models	12
2.8.2 Submicroscopic Simulation Models	12
2.8.3 Cellular Automaton Models	13
2.8.4 Particle Hopping Models	14
2.8.5 Mesoscopic Simulation Models	14

2.8.5.1 Head way Distribution Models	14
2.8.5.2 Cluster Models	15
2.8.5.3 Gas Kinetic Continuum Models	15
2.8.6 Continuum Microscopic Traffic Flow Models	16
2.9 Simulation Packages	17
2.9.1 Paramics vs. VISSIM	17
2.9.2 Classification with Traffic Conditions	18
 Chapter Three – Theoretical Background	 20-28
3.1 Car Following Methods	20
3.2 Gap Acceptance	21
3.3 Stochastic Approach	21
3.4 Queuing Theory	23
3.5 Validation	23
3.5.1 Multistage Validation Frame work	24
3.5.1.1 Conceptual Validation	25
3.5.1.1.1 Model Survey	25
3.5.1.1.2 Model Walkthrough	26
3.5.1.2 Operational Validation	26
3.5.1.2.1 Comparing Two Means	27
3.5.1.3 Data Collection	28
 Chapter Four – Simulation Model	 29-46
4.1 Introduction	29
4.2 Model Development	29
4.3 Logical Development	30
4.3.1 Uncontrolled Intersections	30
4.3.2 Controlled Intersections	31
4.4 Variables Considered	35
4.4.1 Geometric Properties	35
4.4.2 Vehicle Properties	36

4.4.3 Driver Behaviours	37
4.5 Features of the Model	38
4.5.1 Start Form	38
4.5.2 Intersection Selection Form	39
4.5.3 Input Form	40
4.5.4 Signal Phasing Input form	42
4.5.5 Output Form	45
 Chapter Five	
– Surveys for Validation	47-50
5.1 Classified Vehicle Counts	47
5.1.0 Introduction	47
5.1.1 Objective	47
5.1.2 Location	47
5.1.3 Vehicle Classification	48
5.1.4 Survey Procedure	48
5.2 Delay Survey	49
5.2.1 Location	49
5.2.2 Survey Procedure	50
 Chapter Six	
– Analysis of Simulation	51-59
6.1 Introduction	51
6.2 Definition of the Delay	51
6.2.1 Uncontrolled Intersections Simulation	51
6.2.2 Controlled Intersection Simulation	53
6.3 Actual Delay Calculated	54
6.4 Actual vs Simulated Delays in Four-way intersections	54
6.5 Simulated controlled vs Simulated uncontrolled	55
6.6 Validation of the Model	57

Chapter Seven	– Conclusions and Recommendations	60-62
7.1	Conclusions & Recommendations	60
	References	63
	Annex A	65
	Annex B	66



List of Figures

	Page
Figure 1-a Basic Driver Perception-action Process	3
Figure 1-b The Vehicle Object's Interactions in a Simulation System	4
Figure 2.1 Graphic Presentation of Simulation Results in late 60's	8
Figure 3.1 Gap Acceptance	21
Figure 3.2 Multistage Validation Framework	24
Figure 4.0 Flow Chart of the Simulated Model	32
Figure 4.1 Intersections Available in the Simulation Model	35
Figure 4.2 Start Form of the simulation Software	38
Figure 4.3a Intersection Selection Form –Four-Way	39
Figure 4.3b Intersection Selection Form- Three-Way	40
Figure 4.4a Input Form	40
Figure 4.4b Error Message for Simulation Duration	41
Figure 4.5 Signal Phasing Scheme Selection Form	42
Figure 4.6 Controlled Intersection	43
Figure 4.7a Approach Three Vehicles Moving	44
Figure 4.7b Approach Two and Four Vehicles Moving	44
Figure 4.8 Vehicles Moving in Uncontrolled Intersection	45
Figure 4.9 Out-put Form	46
Figure 6.1 Actual Delays vs. Simulated Delays	55
Figure 6.2 Simulated Controlled vs. Uncontrolled Intersection Vehicular Delay	56
Figure 6.3 Traffic Stream Flow and Q-K Diagram	57

List of Tables

	Page
Table 2.1 Comparison of Simulation and Conventional Traffic Planning Packages	17
Table 2.2 Comparison of Paramics vs. Vissim	18
Table 2.3 Four Types of Model Classification	19
Table 4.1 Vehicle Types Available in the Simulation	36
Table 4.2 Vehicle Types and Their Characteristics	37
Table 5.1 MCC Data	49
Table 5.2 Calculated Actual Delays on Delay Survey	50
Table 6.1 Simulated Uncontrolled Intersection Delay	53
Table 6.2a Simulated Delays of Controlled Intersection	53
Table 6.2b Signal Timing for Two Phase System	53
Table 6.3 Average Vehicular Delays in Approach Roads in the Bellanthara Junction	54
Table 6.4 Average Actual Delays and Average Simulated Delays for each Approach	56
Table 6.5 Total Theoretical Delay Calculation Table	57
Table 6.6 Simulated vs. Theoretical Delays at Controlled Intersection	58



Table 6.7	Simulated Average Delays at Bellanthara Junction	58
Table 6.8	Actual Average Delays at Bellanthara Junction	58



List of Annexes

		Page
Annex A	Delay Survey Form	65
Annex B	Manual Classified Counts Form	66



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk